


# Heitmann und Bruun GmbH

## Ihr Partner für die Antriebs- und Fördertechnik

### STIRNRADSCHLEIBEN

	Zahnbreite "B" mm
Modul 3,0	30
Modul 4,0	40
Modul 5,0	50
Modul 6,0	60

Werkstoff C 43



	Modul 3,0				Modul 4,0				Modul 5,0				Modul 6,0			
	de	dp	dm	D1	de	dp	dm	D1	de	dp	dm	D1	de	dp	dm	D1
28													180,0	168,0		25
30													192,0	180,0		25
32									170,0	160,0		25	204,0	192,0		25
35									185,0	175,0		25	222,0	210,0		25
38					160,0	152,0		25	200,0	190,0		30	240,0	228,0		25
40					168,0	160,0		25	210,0	200,0		30	252,0	240,0		25
45					188,0	180,0		25	235,0	225,0		30				
48					200,0	192,0		25	250,0	240,0		30				
50	156,0	150,0		25	208,0	200,0		25	260,0	250,0		30				
52	162,0	156,0		25	216,0	208,0		25	270,0	260,0		30				
55	171,0	165,0		25	228,0	220,0		25	285,0	275,0		30				
57	177,0	171,0		25	236,0	228,0		25	295,0	285,0		30				
60	186,0	180,0		25	248,0	240,0		25	310,0	300,0		30				
65	201,0	195,0		25	268,0	260,0		25	335,0	325,0		30				
70	216,0	210,0		25	288,0	280,0		25	360,0	350,0		30				
72	222,0	216,0		25												
75	231,0	225,0		25	308,0	300,0		25	385,0	375,0		30				
76	234,0	228,0		25	312,0	304,0		25	390,0	380,0		30				
80	246,0	240,0		25	328,0	320,0		25	410,0	400,0		30				
85	261,0	255,0		25	348,0	340,0		25	435,0	425,0		30				
90	276,0	270,0		25	368,0	360,0		25	460,0	450,0		30				
95	291,0	285,0		25	388,0	380,0		25	485,0	475,0		30				
100	306,0	300,0		25	408,0	400,0		25	510,0	500,0		30				
110	336,0	330,0		25	448,0	440,0		25	560,0	550,0		30				
114	348,0	342,0		25	464,0	456,0		25	580,0	570,0		30				
120	366,0	360,0		25												
127	387,0	381,0		25												

Alle Angaben ohne Gewähr